Mark E. Hallenbeck

Washington State Transportation Center (TRAC)
University of Washington
Seattle, WA USA



 An update of the existing <u>guidance</u> provided by FHWA

Intended primarily for state highway agencies

Applicable to all highway agencies



• TMG Covers:

Volume

Vehicle Classification

Vehicle weights



TMG designed

To describe "good practice"

To provide flexibility at the state level

To improve quality of available data, particularly truck information



All program elements (volume, class, and weight) require

Continuous count programs

Geographic coverage



- A good count program includes:
 - HPMS sample data collection
 - Coverage or obsolescence counts
 - Project specific counts

Pavement design

Traffic operations

Other special needs (including other statistical samples)



 Collect classification count data (in place of simple volume counts) whenever possible

- Rules of thumb:
 - 30 percent of all counts should be classification counts
 - At least one classification count per "road"



Data sharing and cooperation between agencies is necessary to

- Improve the availability of data
- Improve the quality of data
- Reduce the cost of data collection



Continuous count program

 Supplies temporal data needed to understand the differences between short duration and annual conditions

Should get this data from more than the traditional ATR program



Continuous Counts – Where Else to Get This Data?

 Use of ITS surveillance data, especially in high volume urban locations

Use of continuous classifiers and WIM devices

Use of other agency's data collection devices



Short Duration Counts

Require adjustments

Axle correction (when appropriate)

Day of week

Season

Time of day (for less than 24-hour counts)



- Short Duration Count Program Design
 - Determine agency specific statistical sample needs and locations
 - Determine HPMS needs and locations
 - Determine project specific needs and locations
 - Compare and coordinate needs
 - Add in additional coverage/obsolescence requirements
 - Schedule counts for efficient manpower / equipment use



HPMS

- No change in HPMS counting requirements
- State highway agencies are responsible for HPMS counts, regardless of whether they actually collect them or not
- Maintain both HPMS sample and universe count information



More emphasis is being placed on truck counts

Importance of trucks to

Pavement design and maintenance

Economic vitality of each state

Increasing role in prioritizing road improvements



Intent

All highways should have valid, accurate, reliable truck usage information



States Need Continuous Classification Counts

Provides measures of

Day of week variation


Seasonal variation

Time of day variation


 Continuous classification counters can replace traditional ATRs



Common Day of Week Volume Patterns



Common Monthly Volume Patterns By Class



 States need to develop a factoring approach that accounts for truck variability, not just volume variability

 TMG recommends developing trucking movement specific factoring process



 Continuous classification program should be roughly the size of the ATR program

One counter can serve both purposes



Truck volume factoring process

- Define trucking movements and their variability
 - Urban versus rural
 - Geographic differences
 - Natural resources
 - Economic (industry versus agricultural)
 - Roadway movements (through versus local)



Example Truck Factor Groups

- Rural Roads
- Interstates
- Northern Rural Roads with limited through movements
- Southern Rural Roads with limited through movements
- Rural Roads with large through movements

- Urban Roads
- Urban roads with large through movements
- Interstates and other freeways serving primarily local traffic
- Other urban roads

Short Duration Counts

 Many agencies need to increase the number of classification counts they take

Rules of thumb:

30 percent of counts taken should be classification counts

Every road should have one classification count each year



FHWA 13 Category classes are the preferred system

 Not all data must be collected or should be reported using this system

 Subsets of, or alternatives to, this system can be used where appropriate



- When are different classification schemes OK?
 - Where equipment limitations prevent it
 Loop based permanent classifiers (urban freeways)
 - Summary reports to users
 - Where statistical reliability in factoring is needed
- Agencies must understand how different classification schemes relate to each other



Highway agencies need to thoroughly test their classification algorithms

- Validate basic algorithm
- Test each new batch of equipment
- Understand how different algorithms relate
- Perform calibration and quality control tests



 Understand, report, and teach the difference between:

- Average annual weekday truck traffic
- Average annual daily truck traffic
- Daily truck traffic
- Truck percent
- Peak period truck percent



Intent

Each highway should have accurate reliable truck weight information

- Gross vehicle weights
- Axle weight distributions
- Truck volumes



TMG Recommends:

Creation of "Truck Weight Roadway Groups"



Truck weight roadway groups

 Each road in the group should experience trucks with similar loading patterns

That is, the loading pattern per truck class should be the same



Example Truck Weight Roadway Groups

- Rural Roads
- Interstates and other roads serving primarily through traffic
- Northern (agricultural area) roads
- Southern (resource extraction) roads

- Urban Roads
- Interstates
- Interstates and freeways serving primarily local traffic
- Roads primarily serving ports
- Roads that serve primarily through traffic
- Other urban roads

 State highway agencies can design their own truck weight roadway groups

Data should be collected to define those groups

States can work together to collect data cooperatively



Truck weight roadway groups should be easily identified and applied by users

- The initial key is to define roads with high loading factors from those with low loading factors
 - (NOT high volume versus low volume)



- Data collection within each group
 - Should consist of multiple sites (rule of thumb: six sites per group)
 - Should include at least one continuous WIM location

(Continuous counter can serve as a continuous classifier and as an ATR)



 State agencies are encouraged to spend more time on collecting good data and less time on collecting data at many locations

- Equipment calibration
- Equipment/site maintenance
- Quality control procedures



Care should be taken trading off

- Number and variety of locations (geographic knowledge)
- Duration of counts (temporal variation)
- Quality of data
- Resources required (staff and money)



- As equipments / sites fail
 - Consider moving those sites to new data collection locations
 - Value of data at new location versus value of trend information
 - Cost of new site versus repair of old site
 - Work with other agencies to share expenses and data



Collect and report quality data

Work cooperatively

Market your data!



Increase the emphasis on counting truck volumes

Factor truck counts for day-of-week and season

 States can use other classification systems in addition to FHWA's 13-category system



 HPMS Counts should remain the mainstay of statewide traffic counting

 Enough coverage counting should be done to maintain the accuracy of all volume estimates

 Agencies need to obtain, store, and use ITS data to supplement existing programs



 Truck weight program has become less statistically rigorous and more tuned towards the needs of the AASHTO 2002 Pavement Design Guide

 Truck weight program focuses on quality rather than quantity

